



2507 Weighing Machine

Microprocessor controlled non-automatic weighing machine with user friendly LCD display.

This is a twin belt system with fast feed, slow feed and pulse feed to the weighing head. The weighing head is supported on two load cells feeding information back to the processor.

Rubber lined head.

Pneumatic door opening via a foot pedal.

All mounted on four 150mm diameter locking castor wheels with levelling indicator and jacks.

Weighing range: from 5 kilos to 25 kilos
depending on which chute is fitted and type of crop.

Capacity: up to 350 bags per hour
depending on product and pack size.

Power requirement: 3 phase, 4 amps

Weighing 7.05

TONG ENGINEERING LTD

Ashby Road, Spilsby, Lincolnshire, PE23 5DW

Tel: 0044(0) 1790 752771 Fax: 0044(0) 1790 753611

Email: sales@tongpeal.com www.tongeng.co.uk



Weighing & Bagging



Available in varying sizes and configurations, from the 1005 Prepacker from 2 to 10 kilos, to the 5009 up to 50 kilos in a single drop to 1000 kilo batches.

All machines are available either painted, powder coated, hot dipped galvanised or the ultimate stainless steel.

All machines designed to be multi-purpose or tailor made for specific crops or products.



Engineering solutions for increased productivity